




Infra-Red Weather Proof Camera

External Lens
& IR Power Adjustment

Sony Effio
680TVL



Features

CAM78IRHR

Image Sensor, DSP
Picture Elements
Horizontal Resolution
Minimum Illumination
Lens
IR LED Sensor Switchable
IR Distance
IR LED

Sync System
Electronic Shutter
DRN Sense Up
Adjustments
AGC & White Balance
S/N Ratio
Video Output Signal
Operating Temp.
Power Consumption
Dimensions
Water Resistance

Specifications

K-23HCVF-1

1/3" SONY EXview HAD CCD, SONY Effio-E
PAL: 1024(H) x 596(V)
680 TV Lines Colour, 700TV Lines B/W
0.5 Lux @ F1.2 with IR Off / 0 Lux with IR On
3.8mm – 9.5mm Auto Iris Low Lux Lens
CDS Auto Switched
Up to 20 meters
24 Standard Power LED's
6 Super High Power Reflection LED's
Internal
Auto 1/50 (1/60) – 1/100,000 Sec.
Auto Dynamic Digital Noise Reduction
External Vari-focal Lens & IR LED's Adjustment
Automatic
More than 50 dB (AGC Off)
Composite BNC Output 1.0Vp-p at 75 Ohm
-10°C -- +50°C
12VDC / 24VAC 450mA
93mm (DIA) x 163mm (L) (w/o Bracket)
IP66

For more information
contact Downs Protection
07 4633 1112
info@downsprotection.com.au

